

Product Name	Clear Mounting Adhesive	
Product Description	Polyester carrier / Acrylic copolymer / Siliconized paper	
Base Material Carrier	Clear Polyester	
	Thickness	23 mic ± 5% (.9 mil)
	Weight (gsm)	33 gsm ± 5%
Adhesive #1	Type of Adhesive	Clear Acrylic
	pH-value	approx. 7.0
	Thickness	25 mic ± 5 (1 mil)
	180° Peel Adhesion (kg/inch) (method:PSTC-1)	1kg/inch
	0° Shear strength (hr/inch) (method: PSTC-7)	54hrs/inch
Adhesive #2	Type of Adhesive	Clear Acrylic
	pH-value	approx. 7.0
	Thickness	25 mic ± 5 (1 mil)
	180° Peel Adhesion (kg/inch) (method:PSTC-1)	1kg/inch
	0° Shear strength (hr/inch) (method: PSTC-7)	54hrs/inch
Release Liner	Type of Release Liner	Two Sided Siliconized Paper
	Release Liner Weight (gsm)	110 gsm ± 5%
	Number for sides PE coated	2
Heat Resistance	Application temperature range:	+5° C to 40° C / 40° F to 104° F
Storage Conditions	18° C to 25° C / 60° F to 80° F; 40-65% relative humidity	
Durability	Up to 2 years, vertical exposure	
Shelf life	1 year in storage conditions	

Refer to GFP "Product Warranty" publication



1148 Rochester Road, Troy, MI 48083
800-260-0839 info@azon.com
www.azonequipment.com