

| | | |
|---------------------|---|------------------------------------|
| Product Name | Texture Matte PVC 5 mil UV | |
| Product Description | PVC Film / Acrylic copolymer / Siliconized paper | |
| Face Material | Calendared Polyvinyl Chloride | |
| | Thickness | 0.125mm±0.005mm (125 ± 5mic) 5 mil |
| | Weight (gsm) | 165 gsm ± 5% |
| | Gloss Level (method: ASTM D-523 - 60°) | 6 |
| Adhesive | Clear acrylic type | |
| | pH-value | approx. 7.0 |
| | Coating thickness | 0.022mm (22mic) .9 mil ± 5% |
| | 180° Peel Adhesion (kg/inch) (method:PSTC-1) | 1kg/inch |
| | 0° Shear strength (hr/inch) (method: PSTC-7) | 54hrs/inch |
| Release Liner | White Siliconized paper | |
| | Weight (gsm) | 105 gsm ± 5% |
| Heat Resistance | Application temperature range: | +5° C to 40° C / 40° F to 104° F |
| Storage Conditions | 18° C to 25° C / 60° F to 80° F; 40-65% relative humidity | |
| Durability | Up to 2 years, vertical exposure | |
| Shelf life | 1 year in storage conditions | |

Refer to GFP "Product Warranty" publication



1148 Rochester Road, Troy, MI 48083
800-260-0839 info@azon.com
www.azonequipment.com